

Tel: 01753 687718

sales@specialistcable.co.uk **www.specialistcable.co.uk**

Bus Cables – E,M,O

Application

Lighting Bus Cables


Suitable for use within Simmtronic Systems

E- Bus- Blue or White

M-Bus- Pink

O-Bus- Pink

CPR Compliant – Class Eca



Construction

Conductor material:	18 AWG (16 / 0.25) Tinned Copper
Insulation material:	LSOH nominal od 2.00mm
Core identification:	1 Pair – Red / Black
Shield material:	Mylar Wrap – none screened
Jacket:	LSOH nominal od 5.9mm

Characteristics

Voltage rating	600V	Capacitance	59 pF/m
Temperature rating	80°C	Impedance	95 Ohm
Insulation DC resistance	>200MΩ*M		
IEC60754 (Halogen Free)	EN50575:2014	Statement of Conformance It is hereby certified that any goods supplied that reference those above, conform to this specification unless otherwise noted. I. Loades Director	
IEC61034 (Smoke Emissions)	CPR Eca		
IEC60332-1 (Flame Propagation)			

**Unit 5, Wycombe Logistics Centre, Lincoln Road,
Cressex Business Park, High Wycombe. HP12 3RB.**

**Unit 16, Cockriden Farm Industrial Estate,
Brentwood Road, Herongate, Brentwood. CM13 3LH.**